



Decorative Paints and Coatings

Amarsis

DESCRIPTION

Acrylic emulsion based, decorative coating with special silver and gold effects.

APPLICATION AREA

AMARSIS adds depth and character to any interior wall. It is used together with the appropriate primer on walls, plaster, concrete and wood surfaces after surface preparation.

SURFACE PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and undercoated with SAN DECO AMARSIS PRIMER.

APPLICATION INSTRUCTIONS

- AMARSIS has two application methods which is done with brush or trowel.
- Brush Application;
The ready-to-use AMARSIS is slowly and softly mixed with a spatula without thinning. During the mixing process do not use mechanical devices. Then it is applied as one coat with special brush. 25 minutes later, use the stainless steel trowel to smooth the decorated surface.
- Then, apply second coat of AMARSIS after 4-5 hours at 23°C with brush. 1 hour later, use stainless steel trowel to make pressure on the surface so that the color particles are crushed and reduced in size, light and dark shades of colors are created.
- Trowel Application,
AMARSIS is applied to surface with steel trowel as one coat.
- Then, after 4-5 hours at 23°C, apply second coat of AMARSIS with the same technique with trowel. 1 hour later, use stainless steel trowel to make pressure on the surface so that the color particles are crushed and reduced in size, light and dark shades of colors are created.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 4 - 5 hours for touch dry and 24-48 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 7,5-9 m² of surface

-1 kg covers 7,5-9 m² of surface

-The paint consumption for 1 m² area is 110-130 ml and 110-130 gr.

STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Amarsis

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



Product Technical Data Sheet No. DP.011.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88