



Decorative Paints and Coatings

Decocam

DESCRIPTION

DECOCAM is an acrylic emulsion based, decorative coating material composed with ready colour glass particles. It is suitable for interior use but there is also exterior version is available.

APPLICATION AREA

It is used in all kinds of interior/exterior surfaces, on mineral surfaces like rough plaster, exposed concrete, surfaces with old paint on it or cement sheet, with its suitable primer.

FEATURES

- Provides a modern look on the applied environments with its sparkling surface
- Due its high vapor permeability, it allows surface to discharge the steam and breathe.
- During application it covers up the faults on the surface with the thick layer of film that forms.
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odour in the application environments with its perfumed feature.

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and surfaces should be primed with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

- After primer application, apply DECOCAM with steel trowel as single coat. DECOCAM can be used without dilution, but water can also be added to achieve the desired consistency for easier application
- Product should be spread in even thickness to the entire surface with steel trowel. Trowel should be cleaned sometimes if it is needed.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 24 hours for touch dry and 48-72 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 0,35 – 0,45 m² of surface

-1 kg covers 0,20 – 0,25 m² of surface

-The paint consumption for 1 m² area is 2500 – 2800 ml and 4500 – 5000 gr.

STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Decocam

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.020.ENG - Rev02 November 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88