



## Interior Products Range

# Baharia

### DESCRIPTION

BAHARIA is an acrylic emulsion based silicone added silky matt decorative interior paint.

### APPLICATION AREA

BAHARIA is applied on properly prepared interior mineral surfaces like rough cast, concrete, cement sheet, plaster panel surfaces and surfaces which have been painted before.

### FEATURES

- Easy to clean,
- The texture it has, gives a silky matt glossiness to the wall.
- High coverage ability featured.
- Highly vapor permeable, it enables the vapor to be thrown out and allows the surface to breathe.
- Water-based, odour-free; it is harmless for human health and environment.

### SURFACE PREPARATION

After removing all kind of dirt, oil, blistered paint and dust from the application surfaces, the defects of the surface should be corrected with SAN DECO ACRYLIC PRIMER INTERIOR. Undercoat the old painted or to-be-painted surfaces with SAN DECO UNIPRIMER.

### APPLICATION INSTRUCTIONS

- Prior to application, dilute BAHARIA with (maximum) 5-10% of fresh water and mix it properly.
- Apply 2 coats with a roller, brush or spraying method and wait minimum 5 hours before applying the second layer.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

### DRYING TIME

At 23°C, touch dry time is in 5-6 hours, complete dry time is in 24 hours.

### THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;  
-1 lt covers 11 – 16 m<sup>2</sup> of surface,  
-1 kg covers 7,5 – 11 m<sup>2</sup> of surface,  
- Consumption for 1 m<sup>2</sup> area is 65-95 ml and 90-135 gr.

### STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight at a temperature between +5°C and +35°C

### HAZARD STATEMENTS

**H317** May cause an allergic skin reaction.

**DEKA BOYA SANAYİ ve TİC. A.Ş.**



## Interior Products Range

# Baharia

### PRECAUTIONARY STATEMENTS

**P261** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P272** Contaminated work clothing should not be allowed out of the workplace.

**P280** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** IF ON SKIN: Wash with plenty of soap and water.

**P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.

**P363** Wash contaminated clothing before reuse.

**EUH208** Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

#### Product Technical Data Sheet No. IP.002.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

**This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.**

#### DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88